

Landa Tuff-Skin™ Hose

For use with: hot or cold water pressure washers


There is no other high-pressure hose as tough as Landa's Tuff-Skin™ hose. When tested to ISO 6945 / DIN 20024, the Tuff-Skin has proven to be seven times more abrasion resistant than standard pressure washer hoses, yet it is 20% more flexible. The Tuff-Skin, with its unique design, has been engineered for a greater continuous temperature range—from -40° to 275°F / 310°F intermittent—and for handling pressures of up to 6,000 PSI.

Beside its maximum-strength Class A ORS (Oil Resistance Standard)—most other brands are Class B—the Tuff-Skin has a “bite-the-wire” coupling that grips the hose better than any other design.

Both single and double-wire braid hoses come with Landa branded durable plastic sleeves on both ends—a 24-inch sleeve on the gun end—for added operator protection against high-pressure bursts.



- **Greater Oil Resistance:** Both the tube and the cover carry the maximum Class A ORS (Oil Resistance Standard) for longer life. Most brands of hose carry only a Class B rating.
- **Higher Temperature Rating:** Tuff-Skin hoses are rated for continuous temperatures up to 275°F / 310°F intermittent.
- **Special Wire Braid:** Unique design of braid gives Tuff-Skin hose added durability, greater working pressure and higher impulse cycle in both the double- and single-wire products.
- **Easily Identified:** Permanently embossed identification makes for easy tracing and owner protection.



- **Certified Burst Protection:** Tuff-Skin meets the stringent UL-1776 safety standards with two hose guards—including a 24-inch sleeve on the gun end—for added operator protection against bursts.
- **Higher Abrasion Resistance:** The Tuff-Skin cover has been specially compounded to deliver 7 times the abrasion resistance of other brands.
- **Additional Flexibility:** Even with extra durability, the braid design allows for 20% more flexibility than other brands.
- **Unique Coupling:** A “bite-the-wire” coupling actually reaches the wire braid for never-slip retention, far superior to the “compression” fittings used on conventional hoses.

Tuff-Skin 2-Wire 6,000 PSI Hose

LANDA®



- Wrapped impression, maximum oil resistant tube and cover
- Landa branded yellow hose guard
- 2-wire protection
- Seven times greater abrasion resistance
- Built to SAE 100R2AT OD dimensions
- 3/8" MPT swivel x 3/8" MPT solid

Part #	Size	Temp	PSI
8.739-071.0	25' x 3/8" ID	275°F	6000
8.739-072.0	50' x 3/8" ID	275°F	6000
8.739-073.0	75' x 3/8" ID	275°F	6000
8.739-074.0	100' x 3/8" ID	275°F	6000
8.739-075.0	150' x 3/8" ID	275°F	6000
8.724-042.0	3/8" (bulk hose)*	275°F	6000

*400 feet per reel

Case Lot

CASE LOT SAVINGS!

8.916-330.0	100' x 3/8" ID	275°F	6000	Case of 40
-------------	----------------	-------	------	------------

Tuff-Skin 1-Wire 4,000 PSI Hose

LANDA®



- Wrapped impression, maximum oil resistant tube and cover
- Landa branded black hose guard
- 20% greater flexibility
- Seven times greater abrasion resistance
- Built to SAE 100R1AT OD dimensions
- 3/8" MPT swivel x 3/8" MPT solid

Part #	Size	Temp	PSI
8.739-025.0	25' x 3/8" ID	275°F	4000
8.739-026.0	50' x 3/8" ID	275°F	4000
8.739-027.0	75' x 3/8" ID	275°F	4000
8.739-028.0	100' x 3/8" ID	275°F	4000
8.739-029.0	150' x 3/8" ID	275°F	4000
8.724-037.0	3/8" (bulk hose)*	275°F	4000

*500 feet per reel

Landa Tuff-Flex Hose

Tuff-Flex hose has the same durable cover as Tuff-Skin with a smaller outside diameter for greater flexibility!

Tuff-Flex 2-Wire 5,000 PSI Hose

LANDA®

Tuff-Flex hose has the same durable cover as the Tuff-Skin hose. A smaller OD allows for even greater flexibility.



- Yellow Landa branded hose guard
- Wrapped impression, maximum oil resistant tube and cover
- 50% greater flexibility
- Seven times greater abrasion resistance
- Economically priced
- 3/8" MPT swivel x 3/8" MPT solid or 1/2" MPT swivel x 1/2" MPT solid

Part #	Size	Temp	PSI
3/8" Hose			
8.739-212.0	25' x 3/8" ID	275°F	5000
8.739-213.0	50' x 3/8" ID	275°F	5000
8.739-214.0	75' x 3/8" ID	275°F	5000
8.739-215.0	100' x 3/8" ID	275°F	5000
8.739-216.0	150' x 3/8" ID	275°F	5000
3/8" Hose - Case Lot <i>CASE LOT SAVINGS!</i>			
8.916-329.0	50' x 3/8" ID	275°F	5000 Case of 75
8.916-331.0	100' x 3/8" ID	275°F	5000 Case of 40
1/2" Hose			
8.739-401.0	50' x 1/2" ID	275°F	5000
8.739-403.0	100' x 1/2" ID	275°F	5000

3/8" Blue Tuff-Flex 2-Wire 6,000 PSI Hose

LANDA®


- Non-marking durable blue cover
- Yellow Landa branded hose guard
- Smooth impression, maximum oil resistant tube and cover
- 50% greater flexibility
- 3/8" MPT swivel x 3/8" MPT solid

Part #	Size	Temp	PSI
8.921-153.0	25' x 3/8" ID	275°F	6000
8.921-154.0	50' x 3/8" ID	275°F	6000
8.921-155.0	75' x 3/8" ID	275°F	6000
8.921-156.0	100' x 3/8" ID	275°F	6000

Tuff-Flex 1-Wire 3,000 PSI Hose

LANDA®

Tuff-Flex hose has the same durable cover as the Tuff-Skin hose. A smaller OD allows for even greater flexibility.



- Black Landa branded hose guard
- Wrapped impression, maximum oil resistant tube and cover
- 50% greater flexibility
- Seven times greater abrasion resistance
- Economically priced
- 3/8" MPT swivel x 3/8" MPT solid or 1/2" MPT swivel x 1/2" MPT solid

Part #	Size	Temp	PSI
3/8" Hose			
8.739-133.0	25' x 3/8" ID	275°F	3000
8.739-134.0	50' x 3/8" ID	275°F	3000
8.739-135.0	75' x 3/8" ID	275°F	3000
8.739-136.0	100' x 3/8" ID	275°F	3000
8.739-137.0	150' x 3/8" ID	275°F	3000
3/8" Hose - Case Lot <i>CASE LOT SAVINGS!</i>			
8.916-335.0	50' x 3/8" ID	275°F	3000 Case of 75
1/2" Hose			
8.739-397.0	50' x 1/2" ID	275°F	3000
8.739-399.0	100' x 1/2" ID	275°F	3000

3/8" Blue Tuff-Flex 1-Wire 4,000 PSI Hose

LANDA®


- Non-marking durable blue cover
- Black Landa branded hose guard
- Smooth impression, maximum oil resistant tube and cover
- 50% greater flexibility
- 3/8" MPT swivel x 3/8" MPT solid

Part #	Size	Temp	PSI
8.921-149.0	25' x 3/8" ID	275°F	4000
8.921-150.0	50' x 3/8" ID	275°F	4000
8.921-151.0	75' x 3/8" ID	275°F	4000
8.921-152.0	100' x 3/8" ID	275°F	4000

HOSE & HOSE REELS

Industrial Garden Hose

LANDA®

Built to last, extra-large 3/4" ID inlet water hose. EPDM cover and tube is perfect for water and provides ozone and heat protection.



- EPDM tube and cover
- Class C oil resistant
- -40°F to 212°F
- Heavy-duty, contractor grade
- Crush resistant fittings

Part #	Old No.	Size	Temp	PSI
8.711-797.0	4-02140025	25' x 3/4" ID	212°F	200
8.711-798.0	4-02140050	50' x 3/4" ID	212°F	200
8.711-799.0	4-02140075	75' x 3/4" ID	212°F	200
8.711-800.0	4-02140099	100' x 3/4" ID	212°F	200

See page 70 for garden hose fittings.

Sandblast Hose

LANDA®

Heavy-duty spiralite hose available preassembled or by the foot.



- 3/4" spiralite sand hose with air hose locking couplers
- -30°F to 130°F

Part #	Old No.	Size: ID	Temp	Description
8.711-809.0	4-02190000	3/4"	130°F	Sand, Spiralite /ft
8.711-839.0	4-02199925	3/4" x 25'	130°F	Assy, Sand, Spiralite 25'
8.711-840.0	4-02199940	3/4" x 40'	130°F	Assy, Sand, Spiralite 40'
8.711-811.0		1"	130°F	Sand, Spiralite /ft

Float Tank Inlet Hose

LANDA®

Float tank connection hoses are completely assembled and ready to go. Don't see the size you need? Call us for special orders.



- Pre-made hose with special float fitting already installed
- 3/8" ID push-on hose
- -40°F to 212°F

Part #	Old No.	Size	Temp	PSI
8.711-773.0	4-02100008	8"	212°F	300
8.711-774.0	4-02100009	11"	212°F	300
8.711-775.0	4-02100013	13"	212°F	300
9.802-257.0	4-02100030	30"	212°F	300
9.802-258.0	4-02100045	45"	212°F	300
8.707-316.0	2-30140	Connector, Fluidmaster Ball Cock		

Push-On Hose

LANDA®

This is a fabric braid hose with a nitrile cover and tube. Easily pushes onto hose barb fitting and good up to 300 PSI.



- Fabric braid
- Nitrile cover
- -40°F to 212°F

Part #	Old No.	Size	Temp	PSI
9.802-254.0	4-02100000	1/4" ID	212°F	300
9.802-259.0	4-02110000	1/2" ID	212°F	300
9.802-261.0	4-02120000	3/4" ID	212°F	300

Vinyl Tubing

LANDA®

This 1/4" x 1/2" clear vinyl tubing is heavier duty than the rest! Thick wall resists kinking. Available in clear or clear-reinforced with a polyester braid.



- Very flexible
- Available by the foot or 100' rolls

Part #	Old No.	Size: ID x OD	PSI	Description
9.802-251.0	4-02080000	1/4" x 1/2"	50	Clear Vinyl /ft
9.802-252.0	4-02090000	1/4" x 1/2"	250	Braided Vinyl /ft

1/4", 3/8" & 1/2" 2-Wire Pressure Loop

The 1/4" ID pressure lines solid/swivel for most any application. The 3/8" ID pressure loops have female JIC on both ends for typical unloader connection hose. All pressure loops rate 5,000 PSI and 275°F.



1/4" ID Pressure Loop

- 1/4" MPT swivel x 1/4" MPT solid
- 1/4" ID two-wire 5,000 PSI
- Any length available



JIC Pressure Loop

- 1/2" female JIC swivels on each end
- 3/8" ID two-wire 5,000 PSI
- Any length available

Part #	Old No.	Size	Description
8.918-180.0		16" x 1/4" ID	1/4" Pressure Loop
8.918-181.0		20" x 1/4" ID	1/4" Pressure Loop
8.918-182.0		26" x 1/4" ID	1/4" Pressure Loop
8.918-183.0		28" x 1/4" ID	1/4" Pressure Loop
8.918-184.0		30" x 1/4" ID	1/4" Pressure Loop
8.918-419.0		36" x 1/4" ID	1/4" Pressure Loop
8.918-187.0		42" x 1/4" ID	1/4" Pressure Loop
8.918-210.0		16" x 3/8" ID	JIC Pressure Loop
8.918-422.0		20" x 3/8" ID	JIC Pressure Loop
8.918-423.0		22" x 3/8" ID	JIC Pressure Loop
8.918-424.0		25" x 3/8" ID	JIC Pressure Loop
8.918-425.0		29" x 3/8" ID	JIC Pressure Loop
8.918-427.0		36" x 3/8" ID	JIC Pressure Loop
8.711-662.0	4-02047738	38" x 3/8" ID	JIC Pressure Loop
8.918-212.0		42" x 3/8" ID	JIC Pressure Loop
8.918-224.0		20" x 1/2" ID	JIC Pressure Loop
8.711-701.0	4-02067722	22" x 1/2" ID	JIC Pressure Loop
8.918-225.0		28" x 1/2" ID	JIC Pressure Loop
8.918-228.0		46" x 1/2" ID	JIC Pressure Loop
8.918-230.0		70" x 1/2" ID	JIC Pressure Loop

Legacy Rawhide Hose


Legacy

Superior abrasion-resistant cover hose for use with: hot or cold water pressure Washer



All standard 3/8" RAWHIDE assemblies include:

- 1 solid end and 1 swivel end
- 8" molded vinyl, color coded bend restrictors (both ends)
- Class A ORS (Oil Resistance Standard) for longer life
- Superior flexibility
- Temperature up to 275°F

Rawhide 1-Wire 4,000 PSI Black Hose

- Durable wrapped finish outer cover

Part #	Old No.	Length	Temp	Working PSI	Approx wt lbs
3/8" Black Hose (wrapped)					
8.739-030.0	158265	25' x 3/8" ID	275°F	4000	6.00
8.901-774.0	158270	30' x 3/8" ID	275°F	4000	7.00
8.901-776.0	158275	40' x 3/8" ID	275°F	4000	10.00
8.739-031.0	158280	50' x 3/8" ID	275°F	4000	12.00
8.739-032.0	158285	75' x 3/8" ID	275°F	4000	17.00
8.739-033.0	158290	100' x 3/8" ID	275°F	4000	23.00
8.739-034.0	158295	150' x 3/8" ID	275°F	4000	34.00

8.724-037.0 158200* Per Foot

8.916-353.0 Case of 75 (of 8.739-031.0) - 3/8" x 50 ft Hoses

8.916-355.0 Case of 40 (of 8.739-033.0) - 3/8" x 100 ft Hoses

*500 ft reel, 50 ft incremental lengths (max 3 pieces)

Rawhide Smooth Cover Black Hose

Part #	Length	Temp	Working PSI	Approx wt lbs
3/8" Smooth 3,000 PSI 1-Wire Hose				
8.740-216.0	25' x 3/8" ID	250°F	3000	6.00
8.740-217.0	50' x 3/8" ID	250°F	3000	13.00
8.740-218.0	75' x 3/8" ID	250°F	3000	19.00
8.740-219.0	100' x 3/8" ID	250°F	3000	25.00

3/8" Smooth 4,500 PSI 2-Wire Hose

8.740-220.0	25' x 3/8" ID	250°F	4500	8.00
8.740-221.0	50' x 3/8" ID	250°F	4500	15.00
8.740-222.0	75' x 3/8" ID	250°F	4500	21.00
8.740-223.0	100' x 3/8" ID	250°F	4500	28.00

Legacy Rawhide 2-Wire 3/8" Hose

All black 2-wire Legacy Rawhide hose is now rated at 6,000 PSI!

2-Wire RAWHIDE assemblies include:

- 1 solid end and 1 swivel end
- 6,000 PSI rating - black
- 4,500 PSI rating - blue
- 8" bend restrictors (both ends)
- Superior flexibility
- Beefed up high tensile steel wire braid
- Higher abrasion resistance
- New temperature up to 275°F



Rawhide 1-Wire 3,000 PSI Smooth Non-Marking Hose

ANIMAL FAT RESISTANT

Part #	Old No.	Length	Temp	Working PSI	Approx wt lbs
3/8" Smooth Yellow Hose					
8.901-800.0	158980	50' x 3/8" ID	275°F	3000	12.00
8.901-802.0	158985	75' x 3/8" ID	275°F	3000	17.00
8.901-804.0	158990	100' x 3/8" ID	275°F	3000	23.00
8.705-720.0*	158900	Per Foot			

3/8" Smooth Blue Hose

8.739-148.0	158780	50' x 3/8" ID	275°F	3000	12.00
8.739-149.0	158785	75' x 3/8" ID	275°F	3000	17.00
8.739-150.0	158790	100' x 3/8" ID	275°F	3000	23.00
8.739-369.0	158795	150' x 3/8" ID	275°F	3000	34.00
8.724-371.0*	158700	Per Foot			

3/8" Smooth Gray Hose

8.749-935.0		50' x 3/8" ID	250°F	3000	13.00
8.749-936.0		100' x 3/8" ID	250°F	3000	25.00
8.749-945.0*		Per Foot			

1/4" Smooth Blue Hose

8.901-796.0	158880	50' x 1/4" ID	275°F	3000	8.00
8.901-798.0	158890	100' x 1/4" ID	275°F	3000	16.00
8.705-718.0*	158800	Per Foot			

*500 ft reel, 50 ft incremental lengths (max 3 pieces)

See page 56 for fittings to make custom hose.

Part #	Old No.	Length	Temp	Approx wt lbs
3/8" Black Hose (6,000 PSI) - Wrapped				
8.739-077.0	159565	25'	275°F	9.00
8.739-078.0	159580	50'	275°F	17.00
8.739-079.0	159585	75'	275°F	25.00
8.739-080.0	159590	100'	275°F	33.00
8.739-081.0	159595	150'	275°F	48.00
8.724-042.0*	159300	500'	275°F	

*450 ft reel, 50 ft incremental lengths (max 3 pieces)

Part #	Old No.	Length	Temp	Approx wt lbs
3/8" Blue Hose (4,500 PSI) - Smooth				
8.739-229.0	154415	50'	275°F	17.00
8.739-231.0	154425	100'	275°F	33.00
8.705-651.0*	154400	Per Foot		

*500 ft reel, 50 ft incremental lengths (max 3 pieces)

Legacy Ultima Hose

Legacy

Wrapped cover hose with a smaller outside diameter for even greater flexibility!

All standard Ultima assemblies include:

- 1 solid end and 1 swivel end
- 8" molded vinyl color coded bend restrictors (both ends)
- Wrapped impression, maximum oil resistant tube and cover
- 50% greater flexibility
- Temperature up to 275°F

Ultima 1-Wire 3,000 PSI Black Hose (wrapped)

Part #	Old No.	Description	Approx Wt-lbs
3/8" Black Hose			
8.739-373.0	153550	15' x 3/8" ID	5.0
8.739-142.0	153555	25' x 3/8" ID	7.0
8.901-513.0	153560	30' x 3/8" ID	
8.739-143.0	153570	50' x 3/8" ID	13.0
8.739-144.0	153575	75' x 3/8" ID	19.0
8.739-145.0	153590	100' x 3/8" ID	25.0
8.739-146.0	153595	150' x 3/8" ID	37.0
8.724-047.0	153000*	Per Foot	

*Full Reel – 450 ft, hose only, 50 ft incremental lengths (max 3 pieces)

1/2" Black Hose

8.739-420.0	155425	25' x 1/2" ID	7.50
8.739-421.0	155450	50' x 1/2" ID	14.00
8.739-422.0	155475	75' x 1/2" ID	21.00
8.739-423.0	155499	100' x 1/2" ID	27.00
8.724-067.0	155400*	Per Foot	

*Full Reel – 350 ft, hose only, 50 ft incremental lengths (max 3 pieces)

1/4" Black Hose

8.901-418.0	151025	25' x 1/4" ID	5.00
8.901-423.0	151030	30' x 1/4" ID	6.00
8.901-427.0	151050	50' x 1/4" ID	10.00
8.901-429.0	151075	75' x 1/4" ID	15.00
8.901-430.0	151090	100' x 1/4" ID	20.00
8.724-065.0	151000*	Per Foot	

*Full Reel – 800 ft, hose only, 50 ft incremental lengths (max 3 pieces)

1-Wire Custom Hose Fittings:

These hose fittings can be used with any 1-Wire Per Foot Hose.

Part #	Old No.	Custom Length
3/8" Hose		
8.724-335.0	150232*	add fitting(s) and bend restrictor
8.901-309.0	150205*	add fitting(s) only
1/2" Hose		
8.724-333.0	150220*	add fitting(s) and bend restrictor
8.901-321.0	150222*	add fitting(s) only
1/4" Hose		
8.724-313.0	150210*	add fitting(s) and bend restrictor
8.901-314.0	150212*	add fitting(s) only

*Assembly – Add to cost of custom length (labor & fittings - 1 solid, 1 swivel)



Ultima 2-Wire 5,000 PSI Black Hose (wrapped)

Part #	Old No.	Description	Approx Wt-lbs
3/8" Black Hose			
8.739-222.0	154215	15' x 3/8" ID	5.75
8.739-223.0	154225	25' x 3/8" ID	8.00
8.739-224.0	154250	50' x 3/8" ID	15.00
8.739-225.0	154275	75' x 3/8" ID	22.00
8.739-226.0	154290	100' x 3/8" ID	28.00
8.739-227.0	154294	150' x 3/8" ID	42.00
8.724-052.0	154000*	Per Foot	
8.916-354.0		Case of 75 (of 8.739-224.0) - 3/8" x 50 ft Hoses	
8.916-356.0		Case of 40 (of 8.739-226.0) - 3/8" x 100 ft Hoses	

1/2" Black Hose

8.739-424.0	155725	25' x 1/2" ID	9.25
8.739-425.0	155750	50' x 1/2" ID	18.00
8.739-426.0	155775	75' x 1/2" ID	26.80
8.739-427.0	155790	100' x 1/2" ID	35.50
8.724-068.0	155700**	Per Foot	

*Full Reel – 450 ft per reel, hose only, 50 ft incremental lengths (max 3 pieces)

**Full Reel – 350 ft per reel, hose only (max 3 pieces)

2-Wire Custom Hose Fittings:

These hose fittings can be used with any 2-Wire Per Foot Hose.

Part #	Old No.	Custom Length
3/8" Hose		
8.724-336.0	150204*	add fitting(s) and bend restrictor
8.901-309.0	150205*	add fitting(s) only
1/2" Hose		
8.724-334.0	150224*	add fitting(s) and bend restrictor
8.901-321.0	150222*	add fitting(s) only

*Assembly – Add to cost of custom length (labor & fittings - 1 solid MPT, 1 swivel MPT)

Whitewater® Combination Steam Hose

GOOD YEAR

Good up to 3,000 PSI / 250°F or 350 PSI / 325°F.



- Single high-tensile steel wire braid
- High temperature bend restrictors – both ends
- Seamless innertube
- Solid 3/8" or 1/2" MPT connectors – both ends (Swivel ends NOT available)
- Oil-resistant cover

Part #	Old No.	Length
--------	---------	--------

3/8" Hose

8.901-599.0	153930	30'
8.901-601.0	153950	50'
8.901-598.0	153925	25'
8.901-603.0	153975	75'
8.901-604.0	153990	100'
8.705-643.0	153900*	Per Foot

*Full Reel – 500 ft per reel, hose only, 50 ft incremental lengths (max 3 pieces)

1/2" Hose

8.901-721.0	155625	25'
8.901-723.0	155650	50'
8.901-724.0	155675	75'
8.901-725.0	155690	100'
8.705-678.0	155600*	Per Foot

*Full Reel – 500 ft per reel, hose only, 50 ft incremental lengths (max 3 pieces)

Custom Lengths

Part #	Old No.	Description
--------	---------	-------------

3/8" Hose

8.705-643.0	153900	per ft / hose only
8.901-316.0	150215*	add fitting(s) and bend restrictor
8.901-317.0	150216*	add fitting(s) only

1/2" Hose

8.705-678.0	155600	per ft / hose only
8.901-327.0	150230*	add fitting(s) and bend restrictor
8.901-326.0	150228*	add fitting(s) only

*Assembly – Add to cost of custom length (labor & fittings - 2 solid MPT)

Pulse Hose



- 1,300 PSI working pressure
- Available with either plug-end or open flow with solid/swivel connects
- 3/8" MPT on both styles

Part #	Old No.	Description
--------	---------	-------------

8.711-151.0	381118	18" with Plug End
8.711-153.0	381124	24" with Plug End
8.711-155.0	381128	28" Solid/Swivel - Open
8.711-157.0	381136	36" Solid/Swivel - Open

Hobby Hose

Replacement hose for most hobby pressure washers sold by mass retailers.



- Thermoplastic cover
- Fiber-braid reinforcement
- 2,250 PSI working pressure
- 9,000 PSI burst pressure
- M22 x 1.5 fitting inlet
- 14mm seal cone fits Generac, Excell & Kärcher
- 15mm seal cone fits Campbell, MI-T-M

Part #	Old No.	Seal Cone	ID	Length
8.705-485.0	150245	14mm	1/4"	25 ft
8.705-487.0	150246	15mm	1/4"	25 ft

8.711-531.0	4-02010025M	22mm*	1/4"	25 ft
-------------	-------------	-------	------	-------

NOTE: See Hobby Gun and Lance on page 50.

*Both Ends

Sewer Hose

SUPER FLEXIBLE SEWER LINE HOSE AND COUPLINGS have small outside diameter, allowing hose and nozzles to fit through sewer line. Sewer line has

super tough poly-ether cover over ultra-flexible nylon tube.

(1/8" sewer nozzle and hose will operate through many 1-1/2" lines.) **(Nozzles not included.)**



- 160°F max temperature
- Nylon tube, poly-ether cover
- 1.5 GPM optimum flow 1/8"
- 2.5 GPM optimum flow 1/4"

Part #	Old No.	Description
--------	---------	-------------

1/8" Hose – 4,800 PSI, 1/4" inlet / 1/8" outlet

8.705-601.0	150960	1/8" x 25'
8.705-602.0	150963	1/8" x 50'
8.705-603.0	150964	1/8" x 100'

1/4" Hose – 2,600 PSI, 1/4" inlet / 1/4" outlet

8.705-607.0	150968	1/4" x 50'
8.705-608.0	150970	1/4" x 100'

1/4" Hose – 4,400 PSI, 1/4" inlet / 1/4" outlet

8.705-610.0	150972	1/4" x 50'
8.705-611.0	150973	1/4" x 100'

Hose Bend Restrictors



- Top-quality molded fit bend restrictors
- Fits snugly to prevent kinks near the connectors
- Used on hose assemblies
- Non-slip sure fit
- Easy installation, 325°F

Part #	Old No.	Size	Description
--------	---------	------	-------------

8.705-479.0	150166	5.3"	1/4" 1 wire, Black Vinyl
8.705-476.0	150161	6.0"	3/8" 1 wire, Black Vinyl
8.705-478.0	150164	6.0"	3/8" 2 wire, Red Vinyl
8.705-481.0	150170	7.0"	1/2" 1 wire, Black Vinyl
8.705-480.0	150168	7.0"	1/2" 2 wire, Red Vinyl
8.705-483.0	150174	6.5"	3/8" Combo, Gray Vinyl
8.705-482.0	150172	6.5"	1/2" Combo, Black Rubber

*Insulated Rubber

Orange 600 Sprayer Hose & Ribbed PVC Sprayer Hose

Braid reinforced PVC hose designed specifically for AG/Pest control spraying applications.



- Tough ribbed cover
- Color - orange
- 600 PSI max pressure
- Bulk hose standard in 300' single length coils
- Resists abrasion and UV rays

Part #	Old No.	Description
3/8" Hose - Orange		
8.705-527.0	150630	300' Coil (Single, Uncut Length)
8.901-384.0	150634	50' Length (Bulk)
8.901-385.0	150636	100' Length (Bulk)
8.901-383.0	150632	Per Foot (Minimum 25')
8.724-335.0	150232	1-Wire Custom Hose Fitting
1/2" Hose - Orange		
8.705-523.0	150601	300' Coil (Single, Uncut Length)
8.901-377.0	150603	50' Length
8.901-379.0	150606	100' Length
8.705-524.0	150602	Per Foot (Minimum 25')
8.724-333.0	150220	1-Wire Custom Hose Fitting
3/4" Hose - Orange		
8.705-531.0	150660	300' Coil (Single, Uncut Length)
8.901-386.0	150662	Per Foot (Minimum 25')
8.901-351.0	150295	SO/SW Assy w/o Bend Restrictor

NOTE: All Above Hose Can Be Custom Fitted – with MPT Fittings, Male or Female Garden Hose Solid or Swivel Fittings, with or without Bend Restrictors, etc. Combinations Are Too Numerous To List – CALL FOR CUSTOM ASSEMBLY PRICING!

Garden Hose - Apex Quality

The essential product for pressure washing.



- Rated for cold water use
- Reinforced hose for flexibility & strength in all weather
- Assemblies complete with bend restrictor
- 5/8" or larger ID for full flow
- Choice of commercial or heavy-duty grade
- Commercial grade has machined octagonal "wrench tight" fittings

Part #	Old No.	Length	ID	Grade	Color
8.704-786.0	121315	50'	5/8"	Com	Gray
8.704-787.0	121319	100'	5/8"	Com	Gray
8.704-788.0	121332	50'	5/8"	HD	Lt. Green
8.704-789.0	121336	100'	5/8"	HD	Lt. Green
All Rubber Reinforced Hot Water (160°F) Hose					
8.704-790.0	121344	50'	5/8"	Com	Red
8.704-791.0	121348	50'	3/4"	Com	Red

See page 70 for garden hose fittings.

Cold Weather Garden Hose



- Ideal for outdoor contractors
- Thermostatically controlled - heating element is activated at +/- 35°F temperature and turned off at +/- 40°F ambient temperature
- Heated hose with 110 plug
- Use only with a UL approved GFCI outlet or extension
- 5/8" - 50 ft.
- PVC material FDA approved for potable water
- High-quality brass fittings

Part #	Description
8.749-944.0	50' Cold Weather Garden Hose

See page 70 for garden hose fittings.

"Field" Attachable Couplings

Design and build your own hose or adapt and repair hose in the field (no crimper required).



Couplings for 1 Wire Braid Hose

Part #	Old No.	ID x MPT
8.705-493.0	150502	1/4" x 1/4" – Solid
8.705-495.0	150505	1/4" x 1/4" – Swivel
8.705-496.0	150510	3/8" x 1/4" – Solid
8.705-497.0	150511	3/8" x 3/8" – Solid
8.705-498.0	150513	3/8" x 3/8" – Swivel
8.705-499.0	150515	1/2" x 3/8" – Solid
8.705-500.0	150516	1/2" x 1/2" – Solid
8.705-501.0	150518	1/2" x 1/2" – Swivel

Couplings for 2 Wire Braid Hose

Part #	Old No.	ID x MPT
8.705-502.0	150532	1/4" x 1/4" – Solid
8.705-503.0	150535	1/4" x 1/4" – Swivel
8.705-504.0	150540	3/8" x 1/4" – Solid
8.705-505.0	150541	3/8" x 3/8" – Solid
8.705-506.0	150543	3/8" x 3/8" – Swivel
8.705-507.0	150546	1/2" x 1/2" – Solid
8.705-508.0	150548	1/2" x 1/2" – Swivel

Connector Hose - 2' - 10'

Connector hose comes with one solid and one swivel end. Note: Add the suffix "B" to the Old Number to include bend restrictors on one end.



Part #	Length	Part #	Length
3/8" Ultima - 2 wire 5,000 PSI			
8.918-271.0	2'	8.918-282.0	7'
8.918-273.0	3'	8.918-284.0	8'
8.918-276.0	4'	8.918-286.0	9'
8.918-278.0	5'	8.918-288.0	10'
8.918-280.0	6'		

NOTE: Add the suffix "B" to the Old No. to include bend restrictors.

Part #	Length	Part #	Length
3/8" Ultima - 1 wire 3,000 PSI			
8.918-253.0	2'	8.918-263.0	7'
8.918-255.0	3'	8.918-265.0	8'
8.918-257.0	4'	8.918-267.0	9'
8.918-259.0	5'	8.918-269.0	10'
8.918-261.0	6'		

NOTE: Add the suffix "B" to the Old No. to include bend restrictors.

Part #	Length	Part #	Length
1/2" Ultima - 2 wire 5,000 PSI			
8.918-292.0	2'	8.918-301.0	7'
8.918-294.0	3'	8.918-302.0	8'
8.918-296.0	4'	8.918-303.0	9'
8.918-298.0	5'	8.918-304.0	10'
8.918-300.0	6'		

NOTE: Add the suffix "B" to the Old No. to include bend restrictors.

Part #	Length	Part #	Length
1/4" Ultima - 1 wire 3,000 PSI			
8.918-240.0	2'	8.918-247.0	7'
8.918-241.0	3'	8.918-248.0	8'
8.918-242.0	4'	8.918-250.0	9'
8.918-243.0	5'	8.918-251.0	10'
8.918-245.0	6'		

NOTE: Add the suffix "B" to the Old No. to include bend restrictors.

Connector Hose / Car Wash Bay Hose - 12' - 25'

All car wash bay hoses come with solid male pipe on both ends. Note: Add suffix "B" to the Old Number to include bend restrictors on one end.



Part #	Length	Part #	Length
3/8" Ultima - 1 wire 3,000 PSI			
8.918-333.0	12'	8.918-346.0	19'
8.918-334.0	13'	8.918-348.0	20'
8.918-336.0	14'	8.918-350.0	21'
8.918-338.0	15'	8.918-352.0	22'
8.918-340.0	16'	8.918-354.0	23'
8.918-342.0	17'	8.918-356.0	24'
8.918-344.0	18'	8.918-358.0	25'

NOTE: Add the suffix "B" to the Old No. to include bend restrictors.

Part #	Length	Part #	Length
1/4" Ultima - 1 wire 3,000 PSI			
8.918-306.0	12'	8.918-320.0	19'
8.918-308.0	13'	8.918-322.0	20'
8.918-310.0	14'	8.918-324.0	21'
8.918-312.0	15'	8.918-325.0	22'
8.918-314.0	16'	8.918-327.0	23'
8.918-316.0	17'	8.918-329.0	24'
8.918-318.0	18'	8.918-331.0	25'

NOTE: Add the suffix "B" to the Old No. to include bend restrictors.

Part #	Length	Part #	Length
3/8" Blue - 1 wire 3,000 PSI			
8.918-360.0	12'	8.918-373.0	19'
8.918-362.0	13'	8.918-375.0	20'
8.918-364.0	14'	8.918-377.0	21'
8.918-366.0	15'	8.918-379.0	22'
8.918-369.0	16'	8.918-381.0	23'
8.918-369.0	17'	8.918-383.0	24'
8.918-371.0	18'	8.918-385.0	25'

NOTE: Add the suffix "B" to the Old No. to include bend restrictors.

Part #	Length	Part #	Length
1/4" Blue - 1 wire 3,000 PSI			
8.918-387.0	12'	8.918-401.0	19'
8.918-389.0	13'	8.918-403.0	20'
8.918-391.0	14'	8.918-405.0	21'
8.918-393.0	15'	8.918-407.0	22'
8.918-395.0	16'	8.918-409.0	23'
8.918-397.0	17'	8.918-411.0	24'
8.918-399.0	18'	8.918-413.0	25'

NOTE: Add the suffix "B" to the Old No. to include bend restrictors.

Clear Vinyl Tubing

LANDA®



- Also sold in box of 100 ft
- 25°F to 150°F
- Very flexible, non-reinforced
- Packaged in self-dispensing box

Part #	Old No.	ID	OD	WP @70°	Roll Length
9.802-251.0	4-02080000	1/4"	1/2"	100	Sold by the Foot
8.711-733.0		3/8"	1/2"	100	Sold by the Foot

Clear PVC Tubing



- "Box Pak" 100 ft
- 25°F to 150°F
- Very flexible, non-reinforced
- Packaged in self-dispensing box

Part #	Old No.	ID	OD	WP @ 70°F
8.901-279.0	121070	1/4"	3/8"	55
8.704-766.0	121106	1/2"	5/8"	30

Flex Line Bypass / Supply Line Hose

Industrial PVC hose with black seamless inner tube, polyester braid reinforced tough outer cover. Excellent for use as supply lines or bypass lines. Typically used for air hose.



- Looks and feels like rubber
- Smooth dirt- & oil-resistant finish
- Super flexible
- Abrasion-resistant cover
- Burst-rated 3 times WP

Part #	Old No.	ID x OD	WP@70°F	Roll Length
Red Cover, heavy wall				
8.901-281.0	121081	3/8" x .634"	300	50'
8.704-762.0	121084	3/8" x .634"	300	500'
8.901-282.0	121087	1/2" x .792"	250	50'
8.704-764.0	121090	1/2" x .792"	250	500'
8.901-284.0	121097	3/4" x 1.14"	160	50'
8.704-765.0	121099	3/4" x 1.14"	160	300'
Blue Cover, standard wall				
8.704-779.0	121160	1/4" x .475"	250	100'

Clear Reinforced PVC Tubing

Multi-use industrial grade tubing with high resistance to chemicals, solvents & fuel.



- Reinforced with polyester cord
- Huge selection of sizes and lengths
- 4 to 1 burst safety factor

Part #	Old No.	ID x OD	WP@70°F	Roll Length
8.901-256.0	121031	1/4" x 3/8"	250	25'
8.901-257.0	121032	1/4" x 3/8"	250	50'
8.704-751.0	121033	1/4" x 3/8"	250	100'
8.704-752.0	121034	1/4" x 3/8"	250	300'
8.901-260.0	121036	3/8" x 1/2"	175	25'
8.901-261.0	121037	3/8" x 1/2"	175	50'
8.901-262.0	121038	3/8" x 1/2"	175	100'
8.704-753.0	121039	3/8" x 1/2"	175	300'
8.901-264.0	121041	1/2" x 3/4"	175	25'
8.901-265.0	121042	1/2" x 3/4"	175	50'
8.704-754.0	121043	1/2" x 3/4"	175	100'
8.704-755.0	121044	1/2" x 3/4"	175	300'
8.901-263.0		1/2"	175	per ft
8.901-267.0	121046	5/8" x 7/8"	175	25'
8.901-268.0	121047	5/8" x 7/8"	140	50'
8.901-269.0	121048	5/8" x 7/8"	140	100'
8.704-756.0	121049	5/8" x 7/8"	140	300'
8.901-266.0		5/8"	140	per ft
8.901-271.0	121051	3/4" x 1"	140	25'
8.901-272.0	121052	3/4" x 1"	140	50'
8.704-757.0	121053	3/4" x 1"	140	100'
8.704-758.0	121054	3/4" x 1"	140	300'
8.901-270.0		3/4"	140	per ft
8.901-273.0	121059	1" x 1 1/4"	75	25'
8.901-274.0	121060	1" x 1 1/4"	75	50'
8.901-275.0	121061	1" x 1 1/4"	75	100'
8.704-759.0	121063	1" x 1 1/4"	75	200'
8.901-276.0		1"	75	per ft

See page 70 for hose clamps.

Crimp Fittings

Part #	Description	Hose
8.724-027.0	3/8" MPT, Solid	3/8"
8.724-028.0	3/8" MPT, Swivel	3/8"
8.724-029.0	1/2" FJIC, Solid	3/8"
8.706-759.0	3/8" FPT, Swivel	3/8"

LANDA Hose Reels



Extreme Duty. Fully Assembled. Ready to Use!

Landa hose reels were built for the harsh conditions of industrial pressure washer applications. Oversized 100' or 200' reels hold 2-wire 3/8" hose with room to spare. Offering both fixed mount or 360° pivot versions, these reels feature an extended swivel that reduces bends and stress on the hose.

■ *Up to 5,000 PSI and 325°F*

■ *Rugged heavy-duty construction* for commercial applications.

- Heavy gauge steel fabrication
- Gloss black powder coating
- Easy to use brake mechanism reduces unwinding backlash
- Oversized heavy-duty locking mechanism prevents slippage during reel operation
- Large, durable handle

■ *"Flip-Over" hose guide:* Allows ease of use from either side of the reel.

■ *Oversized:* Oversized to easily fit the advertised length of hose. When we say 100' we mean 100+ feet will easily fit.

■ *Rotary mount:* 360 degree rotation with an oversized heavy-duty locking mechanism to prevent the hose from unraveling. Mounts to round or square tubing.

■ *Fully assembled:* Ready to use out of the box. Saves time and money.

Landa Hose Reels

Built for the harsh conditions of industrial pressure washer applications.

LANDA®



Fixed Base Hose Reel



360° Pivot Hose Reel



- 5,000 PSI, 325°F
- 100' and 200' fixed base
- 100' and 200' 360 degree rotating base
- High pressure double seal swivels
- Reels equipped for 3/8" hose. Easily convertible to 1/2" hose with the change to a 1/2" swivel

Part #	Description	Length
8.750-487.0	Pivot Reel	100' x 3/8"
8.750-484.0	Pivot Reel	200' x 3/8"
8.750-477.0	Non-Pivot Reel	100' x 3/8"
8.750-480.0	Non-Pivot Reel	200' x 3/8"

NOTE: Hose not included.

Part #	Description
8.919-430.0	Universal Mount
8.919-794.0	Skid Mount
8.919-437.0	Wall Mount
8.919-434.0	Base Mount
8.919-072.0	Bracket, Universal
8.919-445.0	Bracket, 90-Degree
8.919-441.0	Bracket, 45-Degree
8.919-448.0	Bracket, Vertical

Bracket Sockets



Universal Mount



Skid Mount



Wall Mount



Base Mount

Non-Pivot Reel Brackets



Universal



90-Degree



45-Degree



Vertical

Legacy Hose Reel Swivels

Legacy



- Innovative Design
- 5,000 PSI
- Stainless steel rotor
- Unique dual seal for extra long life
- 2 year warranty



- Limits bend and hose stress
- 5,000 PSI
- Stainless steel rotor
- Unique dual seal for extra long life
- 2 year warranty

Swivels

Part #	Inlet x Outlet
9.118-021.0*	1/2" M x 3/8" F
9.118-022.0	1/2" F x 3/8" F
9.118-023.0	3/8" M x 3/8" F
9.118-024.0	3/8" F x 3/8" F
9.118-025.0	1/2" M x 1/2" F
9.118-026.0	1/2" F x 1/2" F
9.118-027.0	3/8" M x 1/2" F
9.118-028.0	3/8" F x 1/2" F

*Landa Hose Reel Replacement Swivel

Extended Swivels

Part #	Inlet x Outlet
9.118-020.0*	1/2" M x 3/8" F
9.118-029.0	1/2" F x 3/8" F
9.118-030.0	3/8" M x 3/8" F
9.118-031.0	3/8" F x 3/8" F
9.118-032.0	1/2" M x 1/2" F
9.118-033.0	1/2" F x 1/2" F
9.118-034.0	3/8" M x 1/2" F
9.118-035.0	3/8" F x 1/2" F

*Landa Hose Reel Replacement Swivel

Universal Repair Kit

Part #

8.776-001.0



AP Hose Reels

AP hose reels have been designed to perfectly balance ruggedness and durability with affordability.



Swivel Repair Kits

Part #	Old No.
8.900-855.0	110025

- Flared flanges for maximum capacity
- Solid center core for maximum strength
- Rolled beaded edge flanges for maximum safety
- Easy mounting options for maximum versatility
- "Posi-Pin" lock, prevents unwanted dereeling
- Heavy-duty powder-coated steel
- Easy access external swivel
- 4,000 PSI working pressure
- Rated temp: 225°F
- 3/8" or 1/2" inlet/outlet

Part #	Old No.	Hose Dia	Capacity (in feet)	Core Width	Flange Width	Flange Diameter	Overall Height
8.711-192.0	386188	3/8"	50	4.3	7.9	10.5	13.0"
9.804-067.0	386191	3/8"	100	8.7	12.2	10.5	13.0"
8.711-199.0	386206	3/8"	150	6.3	10.2	13.0	16.7"
8.711-201.0	386209	1/2"	100	6.3	10.2	13.0	16.7"
8.712-460.0	421043	Replacement Swivel for Part # 8.711-192.0 & 9.804-067.0					
8.712-469.0	421063	Replacement Swivel for Part # 8.711-199.0					
8.712-462.0	421045	Replacement Swivel for Part # 8.711-201.0					
8.700-188.0	4-0203612	Replacement Handle					

NOTE: Hose is not included in price. See page 59 for connector hose.

- Super-reinforced core, won't collapse!
- Adjustable brake for controlled reel tension
- Convenient external swivel
- Manual rewind handle included
- Solid core bolts onto flanges for extra strength
- 225°F max temperature
- Snap lock to prevent accidental dereeling
- Bearings have oil cap for easy field maintenance
- 4,000 PSI working pressure

Professional Size Reel

Part #	Old No.	Hose Dia	Capacity (in feet)	Reel Size Width	Reel Size Diameter
8.711-182.0	386174	3/8"	150	6"	18"
8.711-183.0	386175	3/8"	300	10"	18"
8.711-184.0	386176	3/8"	350	14"	18"
8.711-189.0	386181	1/2"	200	10"	18"
8.711-190.0	386182	1/2"	270	14"	18"
8.715-921.0	600975T	Replacement Brake for Part # 8.711-182.0 & 8.711-183.0			

NOTE: Hose is not included in price. Interchangeable parts available. Call for pricing. See page 59 for connector hose.

Space Saver Reel

Part #	Old No.	Hose Dia	Capacity (in feet)	Reel Size Width	Reel Size Diameter
8.711-179.0	386171	3/8"	90	6"	14"
8.711-180.0	386172	3/8"	140	10"	14"
8.711-181.0	386173	3/8"	200	14"	14"
8.711-186.0	386178	1/2"	115	10"	14"
8.711-187.0	386179	1/2"	150	14"	14"

NOTE: Hose is not included in price. Interchangeable parts available. Call for pricing. See page 59 for connector hose.



Swivel Repair Kits

Part #	Old No.	Hose Dia
8.700-287.0	075130	3/8"
8.700-285.0	075128	1/2"
8.900-855.0	110025*	

*For Round Swivels

Replacement Swivels – see page 67.

Coxreels Hose Reels



8.711-858.0



9.802-265.0

Spring Driven Hose Reel

- Light weight, compact design
- Adjustable drag brake
- Sturdy U-shaped frame
- Up to 4,000 PSI
- Rolled edges & ribbed discs provide strength & safety
- Pro-grade heavy-duty steel
- 2-year mfg. limited warranty



8.723-649.0
(hose and ball stop not included)

Coxreels offer high performance in a very compact and lightweight hand crank or spring driven hose reel. Perfect for mobile application and permanent floor and wall mount.

- Rated up to 4,000 PSI
- -20°F to 225°F
- Adjustable drag brake
- 90° brass swivel

Part #	Old No.	Description	PSI
8.711-858.0	4-02750001	200' x 1/2" (300' x 3/8" with Adapter)	3000
8.711-860.0	4-02750002	50' x 3/8"	4000
9.802-265.0	4-02750003	100' x 3/8"	4000
8.711-591.0	4-020369	Handle Replacement	
8.711-588.0	4-020366	Locking Pin Assy	
8.723-649.0	87236490	50' x 3/8" Spring Driven	4000
8.705-132.0	140407	1/2" to 3/8" Adapter (for 8.711-858.0)	
8.750-020.0		Ball Stop for 8.723-649.0	
8.711-584.0	4-020362	Replacement Swivel, 1/2"	
8.711-585.0	4-020363	Replacement Swivel, 3/8"	