

31111134151116



Our specially compounded tube is formulated to extend the hose service life in sandblasting hose applications. It is flexible and kink resistant, helping to reduce operator fatigue. The tube and cover are both static dissipating and the 4-ply SBR cover is highly resistant to abrasion and weather conditions. Temperature Rating: -25°F to +180°F

Abrasion Resistance Value ≤ 70mm3 (DIN ISO 4649)

Also Available:

Sandblast Hose Type 334, offering a lightweight, 2-ply cover Gunite Hose Type 847, offering a Tan Pure Gum Tube for highly abrasive materials



Flexible



Static Dissipating



Kink Resistant



Abrasion Resistant

Contact Us:

- 954-785-6760
- sales@hswhite.com
- (9) 1350 S. Dixie Hwy E. Pompano Bch., FL 33060

Hose Type 335 Specs

Part #	I.D. (In)	O.D. (ln)	Plies	W.P. (PSI)	Weight (Lbs / Ft)	Std. Length
335-050	1/2	1.060	2	150	.33	50'/100'
335-075	3/4	1.500	4	150	.64	50'/100'
335-100	1	1.875	4	150	.94	50'/100'
335-125	1-1/4	2.156	4	150	1.14	50'/100'
335-150	1-1/2	2.375	4	150	1.30	50'/100'
335-200	2	2.875	4	150	1.64	50'/100'