



WIRE ANCHOR STROP

ANCHORING 9103

- 6 mm wire
- For around or straight use
- Breaking strength 25 kN

Strong wire sling that is used as a temporary anchor point. Complement the sling with carabiner 012250064 CT, Pillar Steel SG.

SEGMENTS

- ✓ Pitch roof work
- ✓ General industry
- ✓ Tower climber
- ✓ Offshore
- ✓ Confined space
- ✓ Scaffolding
- ✓ Rope access
- ✓ Wind energy

ARTICLES

012255105	ISC, WIRE ANCHOR STROP, 6MM, 1M, PLASTIC COVER
012255110	ISC, Wire Anchor Strop, 6mm, 1,5m, plastic cover
012255113	ISC, Wire Anchor Strop, 6mm, 2m, plastic cover
012255121	ISC, Wire Anchor Strop, 6mm, 3m, with carabiner
012255134	ISC, Wire Anchor Strop, 6mm, 4m, with carabiner
012255148	ISC, WIRE ANCHOR STROP, 6MM, 5M, WITH CARABINER

OVERVIEW

WS is a 6 mm thick wire sling with galvanized wire, plastic cover and aluminum pressed ferrules.

SPECIFICATION

PRODUCT PROPERTIES

Product includes	One wire sling, complement with carabiner 012250064 CT, Pillar Steel SG.
Maximum number of users	2
Maximum load (kg)	240.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Minimum breaking strength - MBS (kN)	25.0
Material	Galvanized steel
Rope	6 mm galvanized wire

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 795 : 2012
Notified body	0102, SGS UK Ltd, Unit 202b Worle Parkway, Weston-superMare, Somerset BS22 6WA, United Kingdom
Other standards	TS 16415:2013

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Warranty	2+1 year when registered in Inspector
Identification	Batch number
RFID	No

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	English (EN)

IMAGES



CRESTO GROUP

Diabasgatan 16
254 68 Helsingborg
Sweden

T. +46 (0)42 563 00
E. support@crestogroup.com
www.crestogroup.com

CRESTO GROUP
EXPECT MORE