LanoPro Multi Grease EPO

Multi-Purpose EP Grease - NLGI 0

Product Data Sheet - 2022.08.04











PURPOSE

PRESSURE

LUBRICATION

Description

LanoPro Multi Grease EPO is a lithium thickened lubricating grease based on mineral oil. The grease contains antioxidants, corrosion inhibitors and EP/AW additives.

The product is a state-of-the-art multi-purpose EP grease which can be used in various applications within given temperature limits. The lubricating grease offers good mechanical stability, load carrying capacity and corrosion protection.

LanoPro Multi Grease EPO is a high quality multi-purpose grease that can be used in marine, industrial and automotive applications. The consistency of the product makes it suitable for use in centralised lubrication systems that require semi-fluid grease.

- Good mechanical stability
- High load carrying capacity
- Good corrosion protection
- Easy to pump at low temperatures

Technical Data

Properties	Test Method	Typical Values
Thickener		Lithium
Base fluid		Mineral oil
Colour	Visual	Yellowish-brown
NLGI grade	ASTM D217	0
Dropping point	IP 396	>160°C
Base oil viscosity at 40°C	ISO 12058	200 mm ² /s
Penetration 60 strokes	ISO 2137	355-385
4-ball weld load	DIN 51350:4	2600 N
Water resistance at 90°C	DIN 51807:1	1-90
Temperature range		-30°C to +120°C Max +130°C

Handling

 Storage Handling and storage temperatures (0°C to 40°C)

 Packaging 18kg - 180kg. Other on request

· Shelf life 5 years

ID No: D 100 159.2

LanoPro Production AS Smedveien 7 1344 Haslum Norway

Phone: +47 40 00 15 14 Fax: +47 21 54 73 43 E-mail: mail@lanopro.com www.lanopro.com

LanoPro Pte Ltd 112 Robinson Road. #12-01

Fax: +65 6826 4109 E-mail: mail@lanopro.com Singapore 068902 www.lanopro.com

Phone: +65 6222 3209