

MINIMAX

MOBILE SERVICES

MINIMAX FIRE EXTINGUISHING UNITS

Minimax Mobile Services GmbH & Co. KG

Minimaxstraße 1
D-72574 Bad Urach
Tel.: +49 (0)7125 154-123
Fax: +49 (0)7125 154-100
exportmobile@minimax.de
www.minimax-mobile.com
www.facebook.com/MinimaxMobileServices

ÜP01FGe February 2020



Experts in fire protection

Minimax Fire Extinguishing Units

		FROSTPROOF FIRE EXTINGUISHING UNITS		FOAM FIRE EXTINGUISHING UNITS			COMPRESSED AIR FOAM FIRE EXTINGUISH-ING UNIT	WATER FIRE EXTINGUISH-ING UNIT	POWDER FIRE EXTINGUISHING UNITS					CARBON DIOXIDE FIRE EXTINGUISHING UNITS			
Type		WS 50 sf	WS 50 sf, ICAO	WS 50 n	WL 50 n	WL 50 nAC	WS 50 n-CAFS	WU 50n	PU 50 s	PM 50 s	PS 50 s	PF 40 m	PF 50 s	C 10	C 20	C 30	C 60
																	
Amount of extin-guishing solution		50 l	50 l	50 l	50 l	50 l	50 l	50 l	50 kg	50 kg	50 kg	40 kg	50 kg	10	20	30	60
Extinguishing agent		frostproof AB-Premix -30	frostproof AB-Premix ICAO	AB-Premix	foam water mixture AFFF	foam water mixture AFFF, alcohol-resistant	AB-Premix	water	ABC dry powder	D dry powder	BC dry powder	BC dry powder	BC dry powder	Carbon dioxide	Carbon dioxide	Carbon dioxide	Carbon dioxide
Propellant		Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	compressed air	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	CO ₂	CO ₂	CO ₂	CO ₂
Operating time approx. s		215	215	215	215	215	130 (wet) 390 (dry)	215	60	40	40	63	40	16	30	41	80
Discharge range approx. m		7	7	7	7,5	7,5	13 (wet) 7 (dry)	7	8	8	8	8	8	3	3	3	3
Operating temper-ature range °C		-30 to +60	-30 to +60	0 to +60	+5 to +60	+5 to +60	0 to +60	+5 to +60	-30 to +60	-30 to +60	-30 to +60	-30 to +60	-30 to +60	-30 to +60	-30 to +60	-30 to +60	-20 to +60
Rating		A	A	A	A	A	A	A	A	-	-	-	-	-	-	-	-
		IV B	B	IV B	IV B	IV B	IV B*	-	IV B	-	IV B	IV B	IV B	B	B	B	B
		-	-	-	-	-	-	-	C	-	C	C	C	-	-	-	-
		-	-	-	-	-	-	-	-	D	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Hose length		dimensionally stable, 10 m	dimensionally stable, 10 m	dimensionally stable, 10 m	dimensionally stable, 10 m	dimensionally stable, 10 m	dimensionally stable, 10 m	dimensionally stable, 10 m	dimensionally stable, 5 m or 10 m	dimensionally stable, 10 m	dimensionally stable, 10 m	dimensionally stable, 10 m	high pressure hose, 6 m	high pressure hose, 6 m	high pressure hose, 6 m	high pressure hose, 6 m or 10 m	high pressure hose, 6 m
Dimensions approx.	height mm	1097	1097	1097	1097	1097	1130	1097	1060	1450	1060	1060	1060	1000	1270	1170	1700
	width mm	485	485	485	485	485	560	485	471	475	471	471	471	455	455	455	640
	depth mm	630	630	630	630	630	470	630	610	575	610	610	610	610	610	720	1250
Weight approx. kg		92	92	90	90	90	94,5	90	92	113	92	82	92	50	72	99	180
Official approval no.		EN 1866-18/00142	special fire extinguisher	EN 1866-18/00144	EN 1866-18/00146	special fire extinguisher	special fire extinguisher	special fire extinguisher	SP 144/10	special fire extinguisher	special fire extinguisher	KB 42/15	special fire extinguisher	P3-3/99	P3-4/99	P3-5/99	P3-11/58
		according to DIN EN 1866-1	similar to standard DIN EN 1866-1	according to DIN EN 1866-1	according to DIN EN 1866-1	similar to standard DIN EN 1866-1	*similar to standard DIN EN 1866-1	similar to standard DIN EN 1866-1	according to DIN EN 1866-1			according to DIN EN 1866-1					
		according to DIN EN 1866-2		according to DIN EN 1866-2	according to DIN EN 1866-2				according to DIN EN 1866-2								
																	