



DUO-SAFETY LADDER - MARINE DIVISION

MHDRGS - Heavy Duty Marine Boarding Ladders

This double rung Grip Strut by Duo-Safety has raised, three diamond grip strut surfaces on all steps to give safe, sure footing. All steps are braced with double aluminum rungs under each grip strut step. Full length aluminum handrails provide extra strength and safety. All fittings are aluminum or plated steel.

Series MHDRGS

Tubular Rail Construction
500 lb Duty Rated
12" Rung Centers
Handrails standard on all lengths

SPECIFICATIONS

SERIES MHDRGS

Size	Overall Length	Width	Rail Size	Rail Size w/Handrail	Weight
20'	21' 1"	23.75"	8.625"	14.625"	150 lbs
22'	23' 1"	23.75"	8.625"	14.625"	162 lbs
24'	25' 1"	23.75"	8.625"	14.625"	175 lbs
25'	26' 1"	23.75"	8.625"	14.625"	186 lbs
26'	27' 1"	23.75"	8.625"	14.625"	198 lbs
28'	29' 1"	23.75"	8.625"	14.625"	210 lbs
30'	31' 1"	23.75"	8.625"	14.625"	225 lbs
32'	33' 1"	23.75"	8.625"	14.625"	240 lbs
34'	35' 1"	23.75"	8.625"	14.625"	255 lbs
35'	36' 1"	23.75"	8.625"	14.625"	265 lbs
36'	37' 1"	23.75"	8.625"	14.625"	278 lbs
38'	39' 1"	23.75"	8.625"	14.625"	290 lbs
40'	41' 1"	23.75"	8.625"	14.625"	300 lbs
45'	46' 1"	23.75"	8.625"	14.625"	353 lbs
50'	51' 1"	23.75"	8.625"	14.625"	408 lbs

Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Spike feet as Standard

Rubber safety shoes optional for hard surface use.

