

Hasselbinnen 11
22869 Schenefeld / Germany
Tel.: + 49 40 866 438 0
Fax: + 49 40 866 438 10
Mail: info@schoenrock-hydraulik.com

SCHOENROCK
ACCESS IN MOTION



Hydraulic Watertight Sliding Door SHIPTIGHT



Technical Data

- Variable door sizes acc. to customers demand
- Available for 0 – 15 m wc
- Pre-mounted, tested compact unit
- Variable sill versions
- No need for straightening the bulkhead
- Shortest possible installation time
- Variable sill version

Advantages

We've made a host of further enhancements to our proven Hydraulic Watertight Sliding Door. All the following features on the SHIPTIGHT model are new:

- Using a Y-section seal makes for optimal equalisation of mounting tolerance when welding in place
- Increased door frame stiffness
- Guide unit is made of rust-proof stainless steel and brass
- Less force needed to close the door
- Easier installation, as new model requires no cylinder or guide rail fastening to bulkhead
- Sealing surface is rust-proofed
- New electrohydraulic motor for the oil pump, which now no longer runs in an oil bath
- This means that variable and also very short opening times, as well as very frequent door operation, no longer present any problem

SCHOENROCK Hydraulik Marine Systems GmbH
www.schoenrock-hydraulik.com