

LAB PACKS

POLY DRUMS



20 Gallon Labpack w screw-top lid (Yellow)

Product Code: PAK20

- Capacity : 20 Gal. / 76 L
- Max. Load Capacity : 125 lbs / 57 kg
- UN/DOT Rating : 1H2/X57/S
- Dimensions : 20 3/4" / 52.7cm (H)
20 3/8" / 51.75cm (Top Dia.)
16 3/4" / 42.55cm (Bottom Dia.)
- Weight : 13 lbs / 5.85 kg
- Compliance : DOT 49 CFR 173.12



30 Gallon Labpack w screw-top lid (Yellow)

Product Code: PAK30

- Capacity : 30 Gal. / 76 L
- Max. Load Capacity : 396 lbs / 180 kg
- UN/DOT Rating : 1H2/Y120/S
- Dimensions : 28 1/4" / 71.76cm (H)
22 1/2" / 57.15cm (Top Dia.)
16 5/8" / 42.23cm (Bottom Dia.)
- Weight : 18 lbs / 6.3 kg
- Compliance : DOT 49 CFR 173.12



UNITED RESOURCES
M.R.O • Safety • Spill Control

www.unitedrm.com.sg



Additional Information for 20 and 30 Gallon Labpack w screw-top lid

[FEATURES]

- Blow-molded HDPE construction; HDPE incinerates completely
- Chemical and weather resistant
- United Nations (UN) Certified to HM-181
- Operating Temperature Range (-300
- Drop Tested – max weight @ 0F (48 hrs)
- Approved for use with Packing Groups I, II, III
- UV Protection Package
- UL 94HB Flammability Rating
- Nestable for ideal storage
- FDA 21 CFR 177.1520 Food Grade Quality
- Stack Test – three high at maximum weight capacity (24 hrs)

[APPLICATIONS]

- Ideal for storage, handling and transportation of hazardous materials
- Also applicable as spill containment, shipping container and for bio-waste disposal and incineration
- For use with smaller, non-damaged bottles, cans, carboys and 5-gallon pails of non-leaking hazardous materials
- If leaking, must pack with sufficient sorbents – NO FREE LIQUIDS



POLY DRUMS

OVERPACKS



65 Gallon Labpack w screw-top lid (Yellow)

Product Code: PAK65

- Capacity : 65 Gal. / 247 L
- Max. Load Capacity : 660 lbs / 300 kg
- UN/DOT Rating : 1H2/X300/S
- Dimensions : 33 ¾" / 85.73cm (H)
27 1/8" / 68.9cm (Top Dia.)
25 15/16" / 65.88cm (Bottom Dia.)
- Weight : 45 lbs / 20.45 kg
- Compliance : DOT 49 CFR 173.25



95 Gallon Overpack w screw-top lid (Yellow)

Product Code: PAK95

- Capacity : 95 Gal. / 360 L
- Max. Load Capacity : 660 lbs / 300 kg
- UN/DOT Rating : 1H2/X300/S
- Dimensions : 41 ¼" / 104.78cm (H)
31" / 78.74cm (Top Dia.)
26 1/16" / 66.2cm (Bottom Dia.)
- Weight : 50 lbs / 22.73 kg
- Compliance : DOT 49 CFR 173.25



UNITED RESOURCES
M.R.O • Safety • Spill Control

www.unitedrm.com.sg



Additional Information for 65 and 90 Gallon Labpack w screw-top lid

[FEATURES]

- Blow-molded HDPE construction; HDPE incinerates completely
- Chemical and weather resistant
- United Nations (UN) Certified to HM-181
- Operating Temperature Range (-300
- Drop Tested – max weight @ 0F (48 hrs)
- Approved for use with Packing Groups I, II, III
- UV Protection Package
- UL 94HB Flammability Rating
- Nestable for ideal storage
- FDA 21 CFR 177.1520 Food Grade Quality
- Stack Test – three high at maximum weight capacity (24 hrs)

[APPLICATIONS]

- Ideal for storage, handling and transportation of hazardous materials
- Also applicable as spill containment, shipping container and for bio-waste disposal and incineration
- For use with larger, non-damaged bottles, cans, carboys and 5-gallon pails of non-leaking hazardous materials
- If leaking, must pack with sufficient sorbents – NO FREE LIQUIDS

SALVAGE DRUMS

POLY DRUMS



65 Gallon Salvage Drum w Metal Band & Bolt (Yellow)

Product Code: SALV65

- Capacity : 65 Gal. / 247 L
- Max. Load Capacity : 440 lbs / 200 kg
- UN/DOT Rating : 1H2/X200/S
- Dimensions : 33 7/8" / 98.74 cm (H)
31" / 78.74 cm (Top Dia.)
26" / 66 cm (Bottom Dia.)
- Weight : 58 lbs / 23.85 kg
- Compliance : DOT 49 CFR 173.3



95 Gallon Salvage Drum w Metal Band & Bolt (Yellow)

Product Code: SALV95

- Capacity : 95 Gal. / 361 L
- Max. Load Capacity : 748 lbs / 340 kg
- UN/DOT Rating : 1H2/X340/S
- Dimensions : 44 3/8" / 112.71 cm (H)
31" / 78.74 cm (Top Dia.)
25 3/4" / 65.41 cm (Bottom Dia.)
- Weight : 58 lbs / 26.1 kg
- Compliance : DOT 49 CFR 173.3



UNITED RESOURCES
M.R.O. • Safety • Spill Control

www.unitedrm.com.sg



Additional Information for 65 and 90 Gallon Salvage Drum x Metal Band & Bolt

[FEATURES]

- Blow-molded HDPE construction; HDPE incinerates completely
- Chemical and weather resistant
- United Nations (UN) Certified to HM-181
- Operating Temperature Range (-300
- Drop Tested – max weight @ 0F (48 hrs)
- Approved for use with Packing Groups I, II, III
- UV Protection Package
- UL 94HB Flammability Rating
- Nestable for ideal storage
- FDA 21 CFR 177.1520 Food Grade Quality
- Stack Test – three high at maximum weight capacity (24 hrs)

[APPLICATIONS]

- Ideal for storage, handling and transportation of hazardous materials
- Also applicable as spill containment, shipping container and for bio-waste disposal and incineration
- For use with damaged or leaking containers of hazardous materials or used absorbent materials contaminated with hazardous substance
- "Salvage Drum" labelling and passed a 3-PSI Pressure Test