

PUMPS

PUMPS**DIAPHRAGM PUMPS, POLYPROPYLENE**

Reliable polypropylene air center section combine with non-metallic clamped casing materials ensure maximum chemical compatibility. Muffler included,

Suitable for clean fluids, slurries or up to 1/8" solids

<u>PART#</u>	<u>SIZE</u>	<u>CONN</u>	<u>FLUID CHAMBER</u>	<u>DIAPHRAGM</u>	<u>USE</u>	<u>WET END</u> <u>REPAIR KIT</u>	<u>AIR</u> <u>REPAIR KIT</u>
72 230	1/2"	NPT	Polypropylene	Geolast	Water/Oil	KIT-PB-05	050075
72 231	3/4"	NPT	Polypropylene	Geolast	Water/Oil	KIT-PB-75	050075
72 232	1/2"	NPT	Polypropylene	Santoprene	Acid/Alkali	KIT-PE-05	050075
72 233	3/4"	NPT	Polypropylene	Santoprene	Acid/Alkali	KIT-PE-75	050075
72 234	1/2"	NPT	Polypropylene	PTFE	Acid/Alkali	KIT-PT-05	050075
72 235	3/4"	NPT	Polypropylene	PTFE	Acid/Alkali	KIT-PT-75	050075
72 236	1/2"	NPT	Conductive Nylon	PTFE	Fuels	KIT-CT-05	050075
72 237	3/4"	NPT	Conductive Nylon	PTFE	Fuels	KIT-PC-75	050075
72 238	1/2"	NPT	PVDF	Santoprene	Acid/Alkali	KIT-KE-05	050075
72 239	3/4"	NPT	PVDF	Santoprene	Acid/Alkali	KIT-KE-75	050075
72 240	1/2"	NPT	PVDF	PTFE	Acid/Alkali	KIT-KT-05	050075
72 241	3/4"	NPT	PVDF	PTFE	Acid/Alkali	KIT-KT-75	050075
72 242	1"	ANSI/DIN	Polypropylene	Santoprene	Acid/Alkali	KIT-PE-10	100
72 243	1-1/2"	ANSI/DIN	Polypropylene	Santoprene	Acid/Alkali	KIT-PE-15	150200
72 244	2"	ANSI/DIN	Polypropylene	Santoprene	Acid/Alkali	KIT-PE-20	150200
72 245	1"	ANSI/DIN	Polypropylene	PTFE	Acid/Alkali	KIT-PT-10	100
72 246	1-1/2"	ANSI/DIN	Polypropylene	PTFE	Acid/Alkali	KIT-PT-15	150200
72 247	2"	ANSI/DIN	Polypropylene	PTFE	Acid/Alkali	KIT-PT-20	150200
72 248	1"	ANSI/DIN	PVDF	PTFE	Acid/Alkali	KIT-KT-10	100
72 249	1-1/2"	ANSI/DIN	PVDF	PTFE	Acid/Alkali	KIT-KT-15	150200
72 250	2"	ANSI/DIN	PVDF	PTFE	Acid/Alkali	KIT-KT-20	150200

PUMPS**DIAPHRAGM PUMPS, ALUMINUM**

Flow rates up to 48 gpm, Air inlet: 1/2"
 max pressure: 120 PSI, Max solids: 1/4",
 max suction lift dry: 17 ft.
 Max suction lift wet: 30 ft.

<u>AIR</u>			<u>FLUID</u>			<u>WET END</u>	
<u>PART#</u>	<u>SIZE</u>	<u>CONN</u>	<u>CHAMBER</u>	<u>DIAPHRAGM</u>	<u>USE</u>	<u>REPAIR KIT</u>	<u>REPAIR KIT</u>
72 260	1/2"	NPT	Aluminum	Geolast	Water	AWE-050-GGPN	AAK-050-A
72 261	1"	NPT	Aluminum	Geolast	Water	AWE-100-GGPNM	AAK-100-A
72 262	1-1/2"	NPT	Aluminum	Geolast	Water	AWE-150-GGPNM	AAK-150-A
72 263	2"	NPT	Aluminum	Geolast	Water	AWE-200-GGPNM	AAK-200-A
72 264	3"	NPT	Aluminum	Geolast	Water	AWE-300-GGPNM	AAK-300-A
72 265	1/2"	NPT	Aluminum	Santoprene	Water//Amonium	AWE-050-SSPE	AAK-050-A
72 266	1"	NPT	Aluminum	Santoprene	Water/Amonium	AWE-100-SSPEM	AAK-100-A
72 267	1-1/2"	NPT	Aluminum	Santoprene	Water/Amonium	AWE-150-SSPEM	AAK-150-A
72 268	2"	NPT	Aluminum	Santoprene	Water/Amonium	AWE-200-SSPEM	AAK-200-A
72 269	3"	NPT	Aluminum	Santoprene	Water/Amonium	AWE-300-SSPEM	AAK-300-A
72 270	1/2"	NPT	Aluminum	PTFE	Fuel/Oil	AWE-050-TTYT-M	AAK-050-A
72 271	1"	NPT	Aluminum	PTFE	Fuel/Oil	AWE-100-TTYT-M	AAK-100-A
72 272	1-1/2"	NPT	Aluminum	PTFE	Fuel/Oil	AWE-150-TTYT-M	AAK-150-A
72 273	2"	NPT	Aluminum	PTFE	Fuel/Oil	AWE-200-TTYT-M	AAK-200-A
72 274	3"	NPT	Aluminum	PTFE	Fuel/Oil	AWE-300-TTYT-M	AAK-300-A

**DIAPHRAGM PUMPS, STAINLESS STEEL**

Flow rates up to 48 gpm, Air inlet: 1/2"
 max pressure: 120 PSI, Max solids: 1/4",
 max suction lift dry: 17 ft.
 Max suction lift wet: 30 ft.

			<u>FLUID</u>			<u>WET END</u>	<u>AIR</u>
<u>PART#</u>	<u>SIZE</u>	<u>CONN</u>	<u>CHAMBER</u>	<u>DIAPHRAGM</u>	<u>USE</u>	<u>REPAIR KIT</u>	<u>REPAIR KIT</u>
72 275	1/2"	NPT	Stainless Steel	PTFE	Acid/Alkali	AWE-050-TT3T-M	AAK-050-A
72 276	1"	NPT	Stainless Steel	PTFE	Acid/Alkali	AWE-100-TT3T-M	AAK-100-A
72 277	1-1/2"	NPT	Stainless Steel	PTFE	Acid/Alkali	AWE-150-TT3T-M	AAK-150-A
72 278	2"	NPT	Stainless Steel	PTFE	Acid/Alkali	AWE-200-TT3T-M	AAK-200-A

PUMPS**1/4" NPT FILTER/REGULATOR/GAUGE AUTOMATIC DRAIN**

Adjust and set air pressure to a set value with a combination filter regulator and pressure gauge unit.

<u>PART#</u>	<u>DESCRIPTION</u>
72 280	For 1/4", 3/8" & 1/2" pump
72 281	For 1-1/2" & 2" pump
72 282	For 3" pump

DRUM KITS

Bung adaptor and 40 inch suction tube

<u>PART#</u>	<u>DESCRIPTION</u>
72 283	For 050 series, Stainless
72 284	For 050 series, Aluminum
72 285	For 050 series, PVDF
72 286	For 050 series, Poly
72 287	For 050 series, Nylon
72 288	For 050 series, PVDF
72 289	For 050 series, Poly
72 290	For 100 series, PVDF
72 291	For 100 series, Poly
72 292	1/2", PDVF
72 293	1/2", Stainless
72 294	1/2", Poly
72 295	1", PDVF
72 296	1", Poly

PUMPS**GREASE LUBRICATOR SET**

Pneumatic grease pump, dust cover, follower plate with Rubber rim, control valve set, Filter/Regulator/Lubricator, Handle mounted on pump to carry unit

<u>PART#</u>	<u>DESCRIPTION</u>
72 010	With 1/4" x 10' H.P. hose

**BARREL PUMP - PNEUMATIC**

A 5:1 pneumatic pump for 55 gal drums with bung adaptor And foot valve.

<u>PART#</u>	<u>DESCRIPTION</u>
72 011	Max air pressure: 120 PSI 1/4" female inlet, Air consumption: 11 CFM

**BARREL PUMPS - BARREL ROTARY**

A steel Barrel rotary pump for 55 gal drums with 6 ft. discharge hose

<u>PART#</u>	<u>DESCRIPTION</u>
72 012	3/4" x 6 foot hose w/curved metal spout Capacity: 8 gallons/min



A Polyethylene Barrel rotary pump for mild chemicals.

<u>PART#</u>	<u>DESCRIPTION</u>
72 013	Three piece suction tube w/curved metal spout and a 2" adjustable bung adapter. Capacity: 8 gallons/min



A Ryton Polyethylene Sulfide rotary pump for aggressive chemicals. All part are made from Stainless Steel. Lip seal Teflon, Viton O-rings

<u>PART#</u>	<u>DESCRIPTION</u>
72 014	Three piece suction tube w/curved metal spout and a 2" adjustable bung adapter. Capacity: 8 gallons/min