## DRY FVOLT



The product is ideal for full removal of any type of moisture caused by seawater.

An invisible nano - film provides protection against corrosion, short circuits and malfunctioning electrical parts for at least two years. The DRY VOLT Marine also prolongs the life of the electrical equipment of each type of Ship - Vessel significantly.

## **Properties**

- Forms a waterproof and water-repellent layer.
- Removes effectively moisture from the surface due to high adhesion and low internal friction.
- Can be applied to damp surfaces.
- Fills tiny grooves.
- Prevents static electricity, dust and dirt.
- Allows the electrical conductivity of the elements in the water.
- It provides high dielectric strength of pipeline.
- Creates an insulating protective layer, preventing the leak of the surface current in the water.
- Does not destroy metals, plastics, rubber, glass, paints, lacquers, ceramics, textiles.
- Prevents and protects against oxidation.

**Use:** Shake well before use. Make sure that there is no electrical power on the surface that the product is going to be applied.

Standby time is approximately 5 minutes.





Application: with portable air HVLP gun, paint brush or Trigger Sprayer.

**Duration of protection:** At least 3-5 years from the date of application provided that the conditions of storage and application rules, and without intensive mechanical stress of the surface -30 °C and +130 °C.

Dielectric Strength: 10.000 Volt

**Ingredients:** It is made from refined high-purity mineral oil, anticorrosive additives, antioxidants.

The product does not contain: rubber, silicone, acrylic, teflon, aromatic compounds, benzene.

Shelf life: Does not expire if lid is not removed.

## Information for safe handling

- Keep away from heat and direct sunlight.
- Away from fire and other ignition sources.
- Store in a cool place.







**Application areas:** motors, transformers, generators, power supply devices, electrical contacts, electronic boards, electrical tools, bulbs, protects from all forms of moisture caused by seawater.























## S. KORKIDIS BROS & CO

HEAD OFFICE: 2-4, FOKIDOS STREET • TEL.: +30 210 4628.372 • FAX: +30 210 4634.314 BRANCH: 27, ARISTIDOU STREET • TEL.: +30 210 4179.407

www.korkidis.gr • e-mail: info@korkidis.gr korkidis@domi.gr



Dry Volt Marine